

## Valve systems ▶ Standardized valve systems

### 5/3-directional valve, Series 581, size 2

▶ Qn = 2100 l/min ▶ plate connection ▶ compressed air connection output: Base plate ISO 5599-1 ▶ Can be assembled into blocks ▶ suitable for ATEX



00132220

Standards	ISO 5599-1
ATEX	2G Ex mb II T42D Ex tD A21 T130°C
Version	Spool valve
Sealing principle	Soft sealing
Blocking principle	Single base plate principle
Working pressure min./max.	-0.95 bar / 16 bar
Ambient temperature min./max.	-20°C / +70°C
Medium temperature min./max.	-20°C / +70°C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 mg/m³ - 5 mg/m³
Pneumatic ports	Base plate ISO 5599-1
Mounting screw	with hexagon socket
mounting screw tightening torque	3.5 Nm
Materials:	
Housing	Aluminum
Seals	Acrylonitrile Butadiene Rubber

#### Technical Remarks

- The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!
- The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C.
- The oil content of compressed air must remain constant during the life cycle.
- Use only the approved oils from AVENTICS, see chapter „Technical information“.

	Flow conductance	Qn	Control pressure min./max.	Weight	Note	Part No.
	C					
	[l/(s*bar)]	[l/min]	[bar]	[kg]		
	9.6	2100	3 / 16	0.42	-	<b>5812430000</b>
	9.6	2100	3 / 16	0.42	1)	5812431000
	9.6	2100	3 / 16	0.42	-	<b>5812530000</b>
	9.6	2100	3 / 16	0.42	1)	5812531000
	9.6	2100	3 / 16	0.42	-	5812730000
	9.6	2100	3 / 16	0.42	1)	5812731000

1) with throttle  
Nominal flow Qn at 6 bar and Δp = 1 bar

**5/3-directional valve, Series 581, size 2**

▶  $Q_n = 2100$  l/min ▶ plate connection ▶ compressed air connection output: Base plate ISO 5599-1 ▶ Can be assembled into blocks ▶ suitable for ATEX

Dimensions

